



MANOIR MARIE

ARTISANALE VLOEREN

HANDICRAFT TERRACOTTA BR-GR

TECHNICAL DATA

2 available sizes:

17cm x 17cm x 2 to 2.5 cm (approx. 34 pieces/m²)

with joint thickness 2 (to 3) mm (as close together as possible)

22cm x 22cm x 2 to 2.5 cm (approx. 20.5 pieces/m²)

with joint thickness 2 (to 3) mm (as close together as possible)

This is a new handmade natural product and therefore the color and size of the tiles may vary slightly within 1 particular lot and between different production lots.



Indoor use and covered terrace

This is a new unique handmade product that can only be manufactured in small volumes: please order in time!

INSTALLING INSTRUCTIONS

- It is of major importance that the tiles are well mixed.
- The tiles can be installed jack-on-jack or in running bond.
- We recommend to keep a joint width of 2 (to 3) mm. The tiles are handmade, may differ slightly in size and a good installation will require just a little more attention and time.
- To be laid in white mortar bed or a thick glue of 1cm.
- It's appropriate to double-glue the tiles, this means put glue on both the tile and the underground.
- Joint color: Always grout up/wash with a "darker cement gray grout color.
- In case of doubt, you may ask the floor layer to perform a sample before jointing the whole surface. We advise to apply a less contrasting joint.
- The joint can always be 1 mm deeper than the tiles, so not level with them. This will keep the shape of the tiles visible whereas the joint remains less apparent.

- Before starting the jointing work, moisten the floor. Joint small surfaces at once and sweep them off regularly in order to avoid cement grout film.
- When the floors are completely dried out, **rub them just 1 time** with an impregnating agent (Funcosil). Since they have already sealed the pores during production, this floor has enough with 1 coat of Funcosil.

Instructions funcosil:

1. Shake the bottles well before use.
 2. We always use a painting roller with bristles and a wide brush.
 3. Pour the product into a container (such a painting tray is most convenient).
 4. Use the brush for the edges and then apply the paint evenly with the roller. Be careful not to apply too much at once to avoid flaking of the product.
 5. If you were to use only a brush, streaks may appear.
 6. Apply the paint both horizontally and vertically.
- Weekly maintenance with a vacuum cleaner and a nourishing soap (Lithofin Wash & Clean) afterwards.
 - Enjoy the beautiful result now!

